



ALPHA MUTT® (2ND GEN) w/ ABS MOBILE UNIVERSAL TRAILER TESTERS



SERVICE-TRUCK MODEL

#5611A-RT8

Complete Diagnostic Trailer Inspection System Purpose-Built for Underbody and Side-Mount Tool Boxes

Features:

- Light Testing
- ABS Diagnostics
- Air Brake Operation
- Cross/Short/Open Diagnostics
- Bluetooth® Equipped
- Digital Readout
- Digital Reporting
- Digital Air Brake and Leakdown Testing
- Anti-Vibration Feet
- Easy-Slide Design
- Soft-Close Drawer

Specifications:

Power: 12/24 V DC
Power Input: Adequate 12V Power Source, i.e., Group 31 Battery or Similar
Output: 20A @ 12/24V DC
Air Input: 120 psi Max. Op. Pressure
Connection Type: 7-Way Round Pin
Controls: Tablet, Remote or Manual
Tablet: 8" Military-Grade
Bluetooth®: 4.0 or Newer
Face Shield: Weather-Proof Steel Door
Display: (2) Dual-Line 32 Character Digital Screens
Design: Anti-Vibration Feet w/ Easy-Slide Box Mount
Materials: Steel Construction
Weight: 54 lbs.
Dimensions: 15.5" W x 21.5" H x 18" D

SHOP MODEL

#5710A-T10

Complete Diagnostic Trailer Inspection System Optimized for Shop Service

Features:

- Light Testing
- ABS Diagnostics
- Air Brake Operation
- Cross/Short/Open Diagnostics
- Bluetooth® Equipped
- Digital Readout
- Digital Reporting
- Digital Air Brake and Leakdown Testing
- Cart with Pneumatic Wheels/Locking Casters

Specifications:

Power: 12/24 V DC
Power Input: Integrated Battery Cabinet Fits 2 Group 31 Batteries (Not Included)
Output: 20A @ 12/24V DC
Air Input: 120 psi Shop Air
Connection Type: 7-Way Round Pin
Controls: Tablet, Remote or Manual
Tablet: 10" Standard
Bluetooth®: 4.0 or Newer
Face Shield: Integrated with Dampeners
Display: (2) Dual-Line 32 Character Digital Screens
Design: Cart w/ 12.5" Pneumatic Wheels & 6" Locking Casters
Materials: Steel Construction
Weight: 85 lbs.
Dimensions: 23" W x 45" H x 22" D

BENCH-TOP MODEL

#5510A-L4T10

Complete Diagnostic Trailer Inspection System with Built-In Battery for Use on Carts, Benchtops and Service Trucks

Features:

- Light Testing
- ABS Diagnostics
- Air Brake Operation
- Cross/Short/Open Diagnostics
- Built-in Lithium Battery
- Bluetooth® Equipped
- Digital Readout
- Digital Reporting
- Digital Air Brake and Leakdown Testing
- Three Mounting Configurations

Specifications:

Power: 12/24 V DC
Power Input: Built-In Lithium Iron Phosphate Battery (LiFePO4)
Output: 20A @ 12/24V DC
Air Input: 120 psi Shop Air
Connection Type: 7-Way Round Pin
Controls: Tablet, Remote or Manual
Tablet: 10" Standard
Bluetooth®: 4.0 or Newer
Face Shield: Integrated with Dampeners
Display: (2) Dual-Line 32 Character Digital Screens
Design: Handles/Brackets with Three Mounting Options
Materials: Steel Construction
Weight: 56 lbs.
Dimensions: 22" W x 31" H x 14" D