

LED Signal Lights - Model 206

PRODUCT INFORMATION

Description	12-24V SAE Double-Sided LED Turn Signal with Guard
Height	124.71 mm / 4.91 in
Width	124.71 mm / 4.91 in
Depth	23.11 mm / 0.91 in
Shape	Round
Outer Lens Material	Polycarbonate
Outer Lens Color	Amber
Housing Material	Polycarbonate
Housing Color	Black
Mounting Type	Hollow Stud Mount
Minimum Operating Temperature	-40 °C / -40 °F
Maximum Operating Temperature	65 °C / 149 °F
Connector or Wiring	12" Bare Leads
Product Weight	0.62 lbs / 0.28 kgs
Shipping Weight	0.91 lbs / 0.41 kgs



ELECTRICAL SPECIFICATIONS

Input Voltage	12-24V DC
Red Wire	Positive
Black Wire	Negative
Current Draw	0.575A @ 12V DC 0.267A @ 24V DC

Print date: 2024-08-11

© 2024 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

LED Signal Lights - Model 206

REGULATORY STANDARDS COMPLIANCE



ASABE S279
Eco Friendly
SAE J974



Buy America Standards
IEC IP67



PHOTOMETRIC SPECIFICATIONS

Beam Pattern(s) Signalization - Turn (Front)
Signalization - Turn (Rear)

APPLICATIONS



Agriculture



Construction



Industrial



Material



Mining



Off-Road 4x4



Railroad



Specialty



Truck & Bus

PRODUCT WARNINGS

For California residents:

WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

Print date: 2024-08-11

© 2024 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

LED Signal Lights - Model 206

RELATED PRODUCTS



Part Number
0341681

12-24V SAE Double-Sided LED Turn Signal without Guard



Part Number
0342771

12-24V ECE/SAE Single-Sided LED Stop & Tail Light without Guard



Part Number
0342781

12-24V ECE/SAE Single-Sided LED Stop & Tail Light with Guard