

150,000 MILE • 5 YEAR PROTECTION

DESCRIPTION

PEAK® Long Life® Antifreeze + Coolant features an extended life coolant technology that is compatible for use in all automobiles, light duty trucks and motorcycles, regardless of make, model, year or original antifreeze color. Its inhibitors provide maximum cooling system protection against damaging rust and corrosion.

FEATURES & BENEFITS

- Compatible for use in all automobiles, light duty trucks and motorcycles
- Provides 150,000 miles or 5 years of maximum protection when a complete cooling system flush and fill is performed
- Meets European phosphate-free and Japanese silicate-free requirements
- Meets ASTM D3306 + ASTM D4985

APPLICATIONS

Engineered for use in all passenger cars, SUVs, motorcycles and light duty trucks, regardless of make, model, year or antifreeze/coolant in the system.

Best performance is achieved when a complete flush & fill is performed using PEAK Long Life Antifreeze + Coolant.



FREEZE/BOIL PROTECTION CHART

Coolant/Water	PROTECTION FROM		
Ratio	Freezing Down to	Boiling Up to*	
50/50	-34°F (-36°C)	265°F (129°C)	
60/40	-62°F (-52°C)	270°F (132°C)	

*At sea level atmospheric pressure with 15lb, pressure cap. The boiling point decreases about 2°F per 1,000 feet of altitude and increases about 2.5°F per pound developed in the system.





PROPERTIES	ASTM Method	TYPICAI CONCENTRATE	VALUES PREDILUTED (50/50)	ASTM D3306 Limits
Appearance/Color	Visual	Fluorescent Yellow	Fluorescent Yellow	Distinctive
Specific gravity	ASTM D1122	1.115-1.124	1.066	1.110-1.145 ¹ / 1.065 min ²
Boiling point ³, °F (°C), 50 vol %	ASTM D1120	325(162.8)	229 (109.5)	226 (108) min
pH, 50 vol %	ASTM D1287	8.3	8.3	7.5-11.0
Effect on Automotive Finish	ASTM D1882	No Effect	No Effect	No Effect
Total water, mass %	ASTM D1123	5	50	5 max¹
Ash content, mass %	ASTM D1119	<5	<2.5	5 max¹ / 2.5 max²
Chloride, ppm	ASTM D3634	<25	<25	25 max
Shelf Life, years- unopened original container		3	5	

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION

FULL STRENGTH CONCENTRATE



PSAOB1 55 Gallon Concentrate Drum 0-74804-03395-3

PRAOB3 1 Gallon Concentrated Bottle 0-74804-00943-9



PSAB51 55 Gallon 50/50 Drum

0-74804-03353-3

PRAB53 1 Gallon 50/50 Bottle 0-74804-00944-6

To order, please call Old World Industries, LLC Customer Service at 1-800-323-8755.

Part #	Unit	Pack/Size	Dimensions	Unit Wt (lbs)	Units per Pallet	Pallets per Truck	Pallet Weight**
PRAOB3	Case	6/1 gal	15.8"L x 12.6"W x 12.25"H	60	36	36	2,210
PRAB53	Case	6/1 gal	15.8"L x 12.6"W x 12.25"H	57	36	36	2,138
PSAB51	Drum	55 gal	23.5" dia. x 34.5"	529	4	20	2,166
PSAOB1	Drum	55 gal	23.5" dia. x 34.5"	553	4	20	2,262

^{**}Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK Long Life Antifreeze/Coolant can be stored in original container at ambient temperature and limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

Safety and Environmental Guidance: PEAK Long Life Antifreeze/Coolant is based on virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from **peakauto.com**. Always dispose of used coolant in accordance with local, state and Federal guidelines.

Old World Industries, LLC Northbrook, IL 60062 • 800-323-5440 Peakauto.com



FILE LOCATION: Mac4/Mac2/PEAK/Antifreeze/Spec Sheets/

PROJECT NAME: 201907_ARF41040_PEAK_LONG LIFE AFC SPEC SHEET FILE NAME: 201907_ARF41040_PEAK_LONG LIFE AFC SPEC SHEET.αi

Project Initiator: Alex

N/A

DESIGNER NAME: Date: **ROUND #:** # ROUNDS SENT TO PRINTER 08/07/19 Amy

FILE SPELL CHECKED	CMYK COLORS	SPOT COLORS	GCMI COLORS	Total Number Of Colors
X 08/07/19	X	PMS 7461 Blue PMS 2935 Blue PMS 2945 Blue PMS 654 Blue PMS 485 Red	0	9
	ATED IN HOUSE PLIED BY CUSTOMER ATED BY AGENCY	Х	RODUCTION	CONCEPT

Questions regarding this artwork, contact: Jill Seminary or Kevin McNeiley in Graphics @ 847-559-2277*

